

TOP-330-2 / MULTI-FUNCTIONAL LABEL DIE CUTTING MACHINE



Cost-efficient die cutting solution for in-mold labels. Offers easy shift from full rotary to semi-rotary, providing high-quality cutting of film material in small quantities. Top-330-2 is a good entry level machine for the in-mold label market. Inline combination available with laminator, slitter and sheeter.

TOP-330-2	
Max Die-cutting Speed (semi-rotary)	60 m/min
Max Die-cutting Length (semi-rotary)	330 mm
Accuracy of Adhesive Cutting	±0.15 mm
Accuracy of IML Cutting	±0.25 mm
Registration	Mark Sensor
Max Web Width	330 mm
Max Unwinder dia.	700 mm
Max Rewinder dia.	700 mm
Standard Magnetic Cylinder	120 T
Total Motor Power	10 kw
Dimension	2500 x 1200 x 2400 mm
Weight	2800 KGS
Power Supply	AV, 380 V, 50 HZ
Air Supply	0.4~0.6 MPa
Min Slitting Width	16 mm




UNWINDER & WEB GUIDING

Independent, servo-driven unwinder with closed-loop tension control. Electronic web guide with ultrasonic edge guide sensor. 76 mm air expanding mandrel. Max diameter 700 mm - 1000 mm roll capacity.

LAMINATOR

Optional, tension-controlled lamination for liner or linerless substrates.




Suitable for both IML and adhesive label



SEMI- OR FULL ROTARY DIE CUTTING

Independent and servo-driven. Repeat lengths from 50 mm - 330 mm for semi-rotary, and 190.5 mm - 476.25 mm for full rotary. Magnetic or solid/engraved cylinders.



IML SYSTEM
IML die-cutting system designed for easy installation and removal. Static eliminator in label output collection table works with counter and step-less speed regulation.



Independent servo driven

REWINDER

Rewinder with closed-loop tension control system ensures continuous stable tension. 700 mm maximum rewind diameter.



COLLECTION TABLE